

Huawei.H12-223.v2022-04-04.q72

Exam Code:	H12-223
Exam Name:	Huawei Certified Network Professional-R&S-IEEP
Certification Provider:	Huawei
Free Question Number:	72
Version:	v2022-04-04
# of views:	275
# of Questions views:	1706
https://www.dumpsfiles.com/files/Huawei/H12-223/Huawei.H12-223.v2022-04-04.q72	

NEW QUESTION: 1

Which of the following link can run PPP instead of HDLC? (Multiple Choice)

- A. ATM
- B. ISDN
- C. PSTN
- D. EI
- E. MSTP

Answer: B,C ([LEAVE A REPLY](#))

NEW QUESTION: 2

When communicating with customers, Huawei engineers need to be groomed, well behaved, and appropriate in language use.

- A. FALSE
- B. TRUE

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 3

Risky operation refers to all operations that may affect the stable running of the device/ proper running of customer services, or normal monitoring on the NMS.

- A. FALSE
- B. TRUE

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 4

Which of the following authorization items is not required for risky operations?

- A. Administrative authorization
- B. Management authorization

- C. Technology authorization
- D. Customer authorization

Answer: A (LEAVE A REPLY)

NEW QUESTION: 5

Which of the following events represent the end of the network planning stage?

- A. Contract signing
- B. Project initiation
- C. Bid release
- D. Preliminary project acceptance

Answer: C (LEAVE A REPLY)

NEW QUESTION: 6

Which of the following statements regarding the device environment check is true?

- A. Devices should be placed stably in flat positions in a ventilated and dry environment, and only a few sundries can be placed around the devices.
- B. For energy saving, the current temperature and humidity in the equipment room must meet requirements of devices. Air conditioners are not required to run continuously and stably.
- C. When the grounding mode and the grounding resistance are checked, the working ground, protection ground, and building lightning protection ground should be separately configured in the equipment room.
- D. It is recommended that power cables and service cables be placed together in a neat and orderly manner.

Answer: C (LEAVE A REPLY)

NEW QUESTION: 7

Which of the following causes may result in an IS-IS neighbor relationship fault? (Multiple Choice)

- A. The devices on two ends of a link have the same system ID.
- B. When an IS-IS Level-1 neighbor relationship is established, the devices on two ends of a link have inconsistent area addresses.
- C. The IP addresses of interfaces on two ends of a link are on different network segments.
- D. The devices on two ends of a link have inconsistent IS-IS levels.

Answer: A,B,C,D (LEAVE A REPLY)

NEW QUESTION: 8

As shown in the figure, all interfaces of the router have ospf enabled. Which one of the following descriptions is correct?

- A. The Type3 LSA generated by R3 in area 0 contains 10.0.2.2/32 routing information
- B. R5 will generate Type3 LSA in area 1

- C. The Type3 LSA generated by R4 in area 1 contains 10.0.2.2/32 routing information
- D. The Type3LSA generated by A.R6 in area 1 contains 10.0.2.2/32 routing information

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 9

Which of the following aspects should be considered for migration risk assessment?

(Multiple Choice)

- A. Loss caused by risks
- B. Risk impact scope
- C. Key risk positions
- D. Risk impact time

Answer: A,B,C,D ([LEAVE A REPLY](#))

NEW QUESTION: 10

Which of the following information can be learned based on the industry background of the project?

- A. Common solutions in the industry
- B. Problems to be resolved by the project
- C. Implementation scope of the project
- D. Organizational structure of customers

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 11

If the number of checked goods is different from the number of goods on the packing list, you can unpack and inspect goods and then contact the vendor to handle the inconsistency.

- A. FALSE
- B. TRUE

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 12

On a campus network, the gateway is usually configured on the aggregation layer. What advantages does this design have compared with configuring the gateway on the access layer? (Multiple Choice)

- A. Allow configuring access devices as Layer 2 devices, reducing network construction costs.
- B. Properly design the Layer 2 network scale, reduce network segment allocation, and improve network management efficiency.
- C. Achieve separate convergence of Layer 2 and Layer 3 to increase the convergence speed and network stability.
- D. Reduce the broadcast domain on the network and the probability of broadcast storms.

E. Leverage the STP and VRRP mechanisms to improve network reliability.

Answer: A,B ([LEAVE A REPLY](#))

NEW QUESTION: 13

Employees in an enterprise often need to connect to the enterprise's intranet for remote access when going on business. Which of the following technologies can meet this demand?

- A. SSL VPN
- B. MPLS VPN
- C. IPSecVPN
- D. ISDN Dial-in

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 14

AR series routers provide various slots. Which of the following is not included?

- A. SIC
- B. XSIC
- C. WSIC
- D. HSIC

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 15

Data center switches greatly differ from campus switches. Which of the following features are specific to data center switches but are not supported by campus switches? (Multiple Choice)

- A. FCoE
- B. TRILL
- C. MSTP
- D. NFV
- E. VxLAN

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 16

During the structured network troubleshooting process, which of the following statements regarding the fault identification phase is true?

- A. Pay attention to user feedback and identify faults based on user feedback.
- B. To minimize the fault effect, try not to let others know the network fault.
- C. Focus on how to better solve faults, regardless of whether a fault is within your own responsibility scope.
- D. Check whether the troubleshooting is within your own responsibility scope.

Answer: D ([LEAVE A REPLY](#))

Valid H12-223 Dumps shared by TrainingDump.com for Helping Passing H12-223 Exam! TrainingDump.com now offer the **newest H12-223 exam dumps**, the TrainingDump.com H12-223 exam **questions have been updated** and **answers have been corrected** get the **newest** TrainingDump.com H12-223 dumps with Test Engine here: <https://www.trainingdump.com/Huawei/H12-223-practice-exam-dumps.html> (165 Q&As Dumps, **40%OFF Special Discount: Exam-Tests**)

NEW QUESTION: 17

In the fault determining and analysis phase of the structured network troubleshooting process, summarizing the fault, maintenance, and change information can obtain a network fault cause list.

- A. FALSE
- B. TRUE

Answer: A (LEAVE A REPLY)

NEW QUESTION: 18

Ethernet is the most mainstream LAN. Which of the following factors should be considered in Ethernet type selection? (Multiple Choice)

- A. Network rate
- B. Encapsulation standard
- C. Network hierarchy
- D. Network scale
- E. Network medium

Answer: (SHOW ANSWER)

NEW QUESTION: 19

Which of the following operations may be needed for checking the service traffic path? (Multiple Choice)

- A. Check the service traffic path at the data link layer.
- B. Survey the service traffic path planning in the network design phase.
- C. Check the service traffic path at the network layer.
- D. Check the fault frequency.

Answer: A,B,C (LEAVE A REPLY)

NEW QUESTION: 20

, well behaved, and appropriate in language use. When communicating with customers, Huawei engineers need to be groomed

- A. TRUE

B. FALSE

Answer: (SHOW ANSWER)

NEW QUESTION: 21

Which of the following aspects should be considered during preliminary analysis of a migration project?

(Multiple Choice)

- A. Costs
- B. Risks
- C. Necessity
- D. Feasibility

Answer: B,C,D (LEAVE A REPLY)

NEW QUESTION: 22

During follow-up operations of the structured network troubleshooting process, which of the following parties does not require advertisement of information?

- A. Authorization parties in each phase of troubleshooting
- B. Other vendors and service providers
- C. Parties affected by the fault
- D. Users who are interested in the root cause for the fault

Answer: D (LEAVE A REPLY)

NEW QUESTION: 23

The customer's project team is the end user of the network, and they are the final judge of the project.

- A. FALSE
- B. TRUE

Answer: A (LEAVE A REPLY)

NEW QUESTION: 24

To improve STP running stability, a network administrator wants to configure some STP features or protection mechanism on switches. Which of the following configuration roadmaps is correct?

- A. Configure BPDU protection so that the switch checks the validity of each received BPDU to prevent attacks of forged BPDUs.
- B. Configure loop protection on positions where loops have occurred so that loops are always blocked.
- C. Configure root protection on the user access port to ensure that the user does not connect to a switch with a higher priority.
- D. Configure the user access port as an edge port to prevent the user from connecting to the switch on this port.

Answer: (SHOW ANSWER)

NEW QUESTION: 25

Which of the following are migration difficulties? (Choose three.)

- A. Achieving optimal risk prevention
- B. Formulating a complete migration solution
- C. Minimizing on services
- D. Carrying out the migration smoothly

Answer: A,B,D (LEAVE A REPLY)

NEW QUESTION: 26

Huawei's enterprise network NMS eSight has three editions: simplified, standard, and professional.

Unlike the standard edition, which of the following features is provided by the professional edition?

- A. Provide a database backup tool.
- B. Support multi-user management
- C. Support management of the WLAN and MPLS VPN
- D. Support hierarchical management model

Answer: D (LEAVE A REPLY)

Explanation/Reference:

NEW QUESTION: 27

On a Layer 2 switching network devices forward data based on MAC addresses.

Therefore, data filtering can be performed based on MAC addresses, and a firewall in transparent cannot filter out Layer 3 information in data packets.

- A. FALSE
- B. TRUE

Answer: A (LEAVE A REPLY)

NEW QUESTION: 28

Which of the following routers provides the cluster function?

- A. AR G3
- B. NE20S
- C. NE40E
- D. NE5000E

Answer: (SHOW ANSWER)

NEW QUESTION: 29

Which of the following causes may result in a BGP peer relationship fault?

- A. The peer connect-interface command is not configured when loopback interfaces are used to establish the BGP peer relationship.
- B. The peer router ID conflicts with the local router ID.
- C. An ACL is configured to disable TCP port 179.
- D. The peer ebgp-max-hop command is not configured when loopback interfaces are used to establish the EBGP peer relationship.

Answer: (SHOW ANSWER)

NEW QUESTION: 30

Which of the following aspects should be considered for migration risk assessment?

- A. Risk impact time
- B. Risk impact scope
- C. Key risk positions
- D. Loss caused by risks

Answer: A,B,C,D (LEAVE A REPLY)

NEW QUESTION: 31

Which of the following causes for VRRP group flapping is the most impossible?

- A. The link where VRRP Advertisement packets are transmitted changes from Up to Down frequently.
- B. VRRP packets are discarded randomly because congestion occurs.
- C. The interval for sending VRRP Advertisement packets is small.
- D. Association between VRRP and BFD is configured to implement a rapid master/backup switchover.

Answer: D (LEAVE A REPLY)

Valid H12-223 Dumps shared by TrainingDump.com for Helping Passing H12-223 Exam! TrainingDump.com now offer the **newest H12-223 exam dumps**, the TrainingDump.com H12-223 exam **questions have been updated** and **answers have been corrected** get the **newest** TrainingDump.com H12-223 dumps with Test Engine here: <https://www.trainingdump.com/Huawei/H12-223-practice-exam-dumps.html> (165 Q&As Dumps, **40%OFF Special Discount: Exam-Tests**)

NEW QUESTION: 32

Huawei's enterprise network NMS eSight has three editions: simplified, standard, and professional. Unlike the standard edition, which of the following features is provided by the professional edition?

- A. Support hierarchical management model.
- B. Support multi-user management.

- C. Support management of the WLAN and MPLS VPN.
- D. Provide a database backup tool.

Answer: A (LEAVE A REPLY)

NEW QUESTION: 33

Which of the following WAN links are used on a packet switched network? (Multiple Choice)

- A. ATM
- B. ISDN
- C. X.25
- D. PSTN
- E. MSTP

Answer: A,C (LEAVE A REPLY)

NEW QUESTION: 34

After PPP Multilink is configured, data is evenly allocated to member links based on the source and destination addresses,

- A. FALSE
- B. TRUE

Answer: A (LEAVE A REPLY)

NEW QUESTION: 35

Upon VRRP group flapping, the vrrp vrid timer advertise command is executed on the router to increase the interval for sending VRRP packets, and then the display vrrp command is executed repeatedly on the backup device to check the State field. It is found that the value of State remains unchanged. Which of the following statements regarding these operations is true?

- A. A small interval for sending VRRP packets may cause status flapping of the backup device.
- B. Status flapping of the backup device is irrelevant to the interval for sending VRRP packets.
- C. The fault cause is not found, and it takes time for the device to recover from the fault.
- D. A large interval for sending VRRP packets may cause status flapping of the backup device.

Answer: A (LEAVE A REPLY)

NEW QUESTION: 36

Which of the following are possible causes for an MSTP failure in a LAN? (Multiple Choice)

- A. MSTP is configured incorrectly.
- B. The MSTP-enabled device receives MSTPTC packets that are transparently sent or from the client.

- C. The priority of the port in the specified MSTE is not configured.
- D. A physical link alternates between Up and Down, triggering the device to send a large number of TC packets.

Answer: A,B,D ([LEAVE A REPLY](#))

NEW QUESTION: 37

Which of the following is not a preliminary preparation for the dry cutover plan?

- A. On-site defense
- B. Overview of the live network
- C. Cutover target
- D. Risk assessment

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 38

The migration rollback time can be determined based on the actual migration situation, without the need to plan in advance.

- A. FALSE
- B. TRUE

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 39

Which of the following statements regarding NMS usage are true? (Multiple Choice)

- A. The NMS supports configuration file management, including automatically backing up, comparing, and restoring the configuration file, allowing the network administrator to configure automatic batch configuration file backup.
- B. The NMS supports alarm management. For example, the Up/Down change of a port can be immediately reported to the NMS through trap, so that the network administrator can discover and rectify network faults in a timely manner.
- C. Based on user requirements, the NMS can generate reports periodically, providing reference for subsequent network optimization.
- D. The NMS supports performance management. It automatically collects statistics about the CPU usage and memory usage of devices, helping the network administrator analyze network performance bottlenecks.

Answer: A,B,C,D ([LEAVE A REPLY](#))

NEW QUESTION: 40

Compared with a three-layer network architecture, a two-layer network architecture has simple topology and high data forwarding efficiency. The network architecture will transform to the two-layer architecture, and the three-layer network architecture will be gradually phased out.

- A. TRUE

B. FALSE

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 41

Which of the following steps or measures are taken in the one-by-one check phase of the structured network troubleshooting process? (Multiple Choice)

- A. Temporary environment setup
- B. Rollback preparation
- C. Contingency plan
- D. Information filter

Answer: B,C ([LEAVE A REPLY](#))

NEW QUESTION: 42

Which of the following statements regarding network maintenance functions are true? (Multiple Choice)

- A. Network maintenance is not just a technical issue but also a management issue.
- B. Through routine maintenance, administrators can obtain the network baseline, laying a good foundation for troubleshooting.
- C. Routine maintenance is a preventive measure.
- D. Routine maintenance has high technical requirements for operators but no high requirements for operation standardization.

Answer: A,B,C ([LEAVE A REPLY](#))

NEW QUESTION: 43

Which of the following subsystems are involved in building cabling? (Multiple Choice)

- A. Vertical subsystem
- B. Backbone subsystem
- C. Horizontal subsystem
- D. Access subsystem
- E. Switching subsystem

Answer: A,C ([LEAVE A REPLY](#))

NEW QUESTION: 44

Which of the following features is not applied to enterprise WANs?

- A. Wide coverage
- B. High costs of utilization
- C. Difficult O&M
- D. Multiple types

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 45

Assume that you received a phone call at your office seat. An employee said he/she could not access the Internet on the PC and needed your technical support. Then you ran the ping command on his/her PC and ran the tracert command to check where packet loss occurred.

Which of the following troubleshooting methods is used in this process?

- A. Bottom-up
- B. Service traffic path check
- C. Top-down
- D. Configuration comparison

Answer: B (LEAVE A REPLY)

NEW QUESTION: 46

Migration rollback is to restore the network state back before the migration.

- A. FALSE
- B. TRUE

Answer: B (LEAVE A REPLY)

Valid H12-223 Dumps shared by TrainingDump.com for Helping Passing H12-223 Exam! TrainingDump.com now offer the **newest H12-223 exam dumps**, the TrainingDump.com H12-223 exam **questions have been updated** and **answers have been corrected** get the **newest** TrainingDump.com H12-223 dumps with Test Engine here: <https://www.trainingdump.com/Huawei/H12-223-practice-exam-dumps.html> (165 Q&As Dumps, **40%OFF Special Discount: Exam-Tests**)

NEW QUESTION: 47

Which of the following is not an external risk to a project?

- A. Differences of industrial standards
- B. Exchange rate change
- C. Rainstorm disaster
- D. Social unrest

Answer: A (LEAVE A REPLY)

NEW QUESTION: 48

Enterprise networks usually use DHCP to assign IP addresses to users. Unlike static IP address assignment, DHCP address assignment greatly reduces the workload for managing network addresses.

- A. TRUE
- B. FALSE

Answer: (SHOW ANSWER)

NEW QUESTION: 49

A network project is often used with the corresponding supporting systems. Which of the following supporting systems are usually included? (Multiple Choice)

- A. Air conditioning system
- B. Power supply system
- C. Transportation
- D. Extra-low voltage cabling
- E. Office equipment

Answer: A,B,D ([LEAVE A REPLY](#))

NEW QUESTION: 50

Which of the following statements regarding the service running status check is true?

- A. You can run the display vrrp and display vrrp statistics commands to check the VRRP status. The value of State should be Initialize.
- B. When checking the multicast forwarding table, you can run the display multicast forwarding-table command to check Layer 2 multicast forwarding entries.
- C. You can run the display current-configuration | include car command to check the attack defense configuration. If attack defense is not configured, run the car command to configure this function.
- D. When checking the multicast routing protocol, you can run the display multicast routing-table command to check the multicast routing table. If PIM-SM is used as the intra-domain multicast routing protocol, multicast interfaces do not need to enable IGMP.

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 51

After the project delivery, the O&M expenses are continuously generated. Which of the following items are the expenses generated during the O&M?

- A. Equipment depreciation expenses
- B. Staff expenses
- C. Line construction expenses
- D. Energy expenses
- E. Line lease expenses

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 52

Current enterprise networks usually use OSPF as the routing protocol. What precautions are there when OSPF is used? (Multiple Choice)

- A. Verify that OSPF costs can correctly demonstrate the actual bandwidth of links at more than 100 Mbit/s.

- B. Check whether secondary optimal routes exist on the network according to OSPF route selection rules.
- C. Check whether all non-backbone areas are correctly and reliably connected to the backbone area.
- D. Determine that the backbone area will not split.
- E. Check the OSPF network topology and ensure that no loop exists when OSPF routes are being calculated.

Answer: A,B,C,D ([LEAVE A REPLY](#))

NEW QUESTION: 53

In most cases, optical power is expressed in dBm. Which of the following values in dBm is supported by most optical transceiver devices to receive and identify data?

- A. 10 dBm
- B. 30 dBm
- C. -10 dBm
- D. -30 dBm

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 54

During follow-up operations of the structured network troubleshooting process, which of the following documents need to be transferred? (Multiple Choice)

- A. User communication plan
- B. Change backup and maintenance suggestions
- C. Troubleshooting summary report
- D. Troubleshooting intermediate documents

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 55

Customer network information and service composition are business secrets of customers and cannot be leaked, obtained without authorization, or sold for operation.

- A. TRUE
- B. FALSE

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 56

Which of the following is the key to network design?

- A. Selection of network elements (NEs) such as devices and links
- B. Performance improvement at reasonable costs
- D Network stability and reliability
- C. Innovation of key technologies

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 57

Which of the following statements regarding the basic device information check is true?

- A. The device time should be consistent with the actual time (time difference \leq 24 hours) so that a fault can be accurately located based on the occurrence time.
- B. You can run the display patch-information command to check patch information.
- C. The debugging functions can be enabled when the device is running properly.
- D. You can run the display current-configuration command to check the PCB version and the software version of a card.

Answer: B (LEAVE A REPLY)

NEW QUESTION: 58

If a fault is located on a router that works in redundancy mode with another router, which of the following methods is the most appropriate for subsequent troubleshooting?

- A. Configuration comparison
- B. Service traffic path check
- C. Top-down
- D. Bottom-up

Answer: (SHOW ANSWER)

NEW QUESTION: 59

Current enterprise networks usually use OSPF as the routing protocol.

What precautions are there when OSPF is used? (Choose four.)

- A. Check the OSPF network topology and ensure that no loop exists when OSPF routes are being calculated.
- B. Check whether all non-backbone areas are correctly and reliably connected to the backbone area.
- C. Check whether secondary optimal routes exist on the network according to OSPF route selection rules.
- D. Determine that the backbone area will not split.
- E. Verify that OSPF costs can correctly demonstrate the actual bandwidth of links at more than 100 Mbit/ s.

Answer: B,C,D,E (LEAVE A REPLY)

NEW QUESTION: 60

In a complex network environment containing finance, OA, production, and more service systems, which of the following items is the first concern for troubleshooting?

- A. IP address assignment
- B. Data flow direction of each servicesystem
- C. Equipment room environment
- D. Network device model

Answer: B (LEAVE A REPLY)

NEW QUESTION: 61

After finding that the OSPF configuration on a router is incorrect, you logged in to the router to check the OSPF configuration. Then you found that the association between OSPF and BFD was also incorrect.

Therefore, you changed the OSPF and BFD configuration. Which of the following troubleshooting methods is used in this process?

- A. Configuration comparison
- B. Segmentation
- C. Bottom-up
- D. Chunking

Answer: D (LEAVE A REPLY)

Valid H12-223 Dumps shared by TrainingDump.com for Helping Passing H12-223 Exam! TrainingDump.com now offer the **newest H12-223 exam dumps**, the TrainingDump.com H12-223 exam **questions have been updated** and **answers have been corrected** get the **newest** TrainingDump.com H12-223 dumps with Test Engine here: <https://www.trainingdump.com/Huawei/H12-223-practice-exam-dumps.html> (165 Q&As Dumps, **40%OFF Special Discount: Exam-Tests**)

NEW QUESTION: 62

Data center switches greatly differ from campus switches.

Which of the following features are specific to data center switches but are not supported by campus switches?

- A. NFV
- B. VxLAN
- C. TRILL
- D. FCoE
- E. MSTP

Answer: B,C,D (LEAVE A REPLY)

NEW QUESTION: 63

Which of the following contents is not negotiated on a project kick-off meeting?

- A. Determine the project management regulations.
- B. Confirm owners of party A and party B.
- C. Determine customer's requirements.
- D. Verify implementation costs.

Answer: D (LEAVE A REPLY)

NEW QUESTION: 64

Generally, which of the following enterprise services require user experience optimization?

- A. Network management
- B. Videoconferencing
- C. Voice call
- D. Video surveillance

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 65

During troubleshooting, you analyze and check the fault cause at the access layer, aggregation layer, and core layer in sequence. Which of the following troubleshooting methods is used in this process?

- A. Bottom-up
- B. Configuration comparison
- C. Segmentation
- D. Chunking

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 66

Which of the following task need to be completed during the planning stage of a project?

- A. Make clear the requirements of a project
- B. Determine the model of networks devices in the project
- C. Plan IP addresses
- D. Work out the technical design
- E. Know the project background

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 67

Which of the following statements regarding the basic device information check is true?

- A. The device time should be consistent with the actual time (time difference < 24 hours) so that a fault can be accurately located based on the occurrence time.
- B. The debugging functions can be enabled when the device is running properly.
- C. You can run the display current-configuration command to check the PCB version and the software version of a card.
- D. You can run the display patch-information command to check patch information.

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 68

Which of the following statements regarding Huawei network optimization service (NOS) is false?

A. Software assessment & recommendation is a technique to assess and analyze all software platforms used by Party A in the service period. Based on the assessment result, this service can recommend a proper software version to prevent issues caused by known issues.

B. Configuration assessment & optimization is a technique to develop and periodically maintain device configuration profiles based on customer requirements. Based on the periodic software assessment & recommendation result, this service applies related software features to command lines in the recommended target version, implementing refined configuration management.

C. Life cycle assessment (LCA) is a technique to check and analyze the software and hardware life cycles of devices on the live network. With LCA, specific measures are taken for products that will reach the end of sales, production, software update, or technical support, preventing life cycle-caused operation risks.

D. Network health check enables Huawei technology experts to review the rationality, security, and scalability of the network architecture based on industry-leading optimal experience, and to provide improvement suggestions based on the assessment result.

Answer: D (LEAVE A REPLY)

NEW QUESTION: 69

When a Huawei router serves as an SSH client and attempts to log in to another Huawei router, the login fails. It is suspected that the SSH server configuration is incorrect.

Which of the following causes is the most impossible for the server fault?

A. The SSH first-time authentication function is disabled.

B. The SSH protocol is not bound in the VTY user interface view.

C. The SSH server and client have inconsistent versions.

D. The user service type, authentication type, and user service type are not configured.

Answer: (SHOW ANSWER)

NEW QUESTION: 70

Which of the following causes may result in an IS-IS neighbor relationship fault?

A. The IP addresses of interfaces on two ends of a link are on different network segments.

B. The devices on two ends of a link have the same system ID.

C. The devices on two ends of a link have inconsistent IS-IS levels.

D. When an IS-IS Level-1 neighbor relationship is established, the devices on two ends of a link have inconsistent area addresses.

Answer: (SHOW ANSWER)

NEW QUESTION: 71

Which of the following causes may result in a BGP peer relationship fault? (Multiple Choice)

- A. The peer ebgp-max-hop command is not configured when loopback interfaces are used to establish the EBGP peer relationship.
- B. The peer connect-interface command is not configured when loopback interfaces are used to establish the BGP peer relationship.
- C. An ACL is configured to disable TCP port 179.
- D. The peer router ID conflicts with the local router ID.

Answer: A,B,C,D ([LEAVE A REPLY](#))

NEW QUESTION: 72

In a complex network environment, the unstructured network troubleshooting process may result in a new fault, making network troubleshooting more difficult.

- A. FALSE
- B. TRUE

Answer: ([SHOW ANSWER](#))

Valid H12-223 Dumps shared by TrainingDump.com for Helping Passing H12-223 Exam! TrainingDump.com now offer the **newest H12-223 exam dumps**, the TrainingDump.com H12-223 exam **questions have been updated** and **answers have been corrected** get the **newest** TrainingDump.com H12-223 dumps with Test Engine here: <https://www.trainingdump.com/Huawei/H12-223-practice-exam-dumps.html> (165 Q&As Dumps, **40%OFF Special Discount: Exam-Tests**)