

## Salesforce.OmniStudio-Developer.v2026-01-02.q113

|                                                                                                                                                                                                                                                   |                                           |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------|
| <b>Exam Code:</b>                                                                                                                                                                                                                                 | OmniStudio-Developer                      |
| <b>Exam Name:</b>                                                                                                                                                                                                                                 | Salesforce Certified OmniStudio Developer |
| <b>Certification Provider:</b>                                                                                                                                                                                                                    | Salesforce                                |
| <b>Free Question Number:</b>                                                                                                                                                                                                                      | 113                                       |
| <b>Version:</b>                                                                                                                                                                                                                                   | v2026-01-02                               |
| <b># of views:</b>                                                                                                                                                                                                                                | 201                                       |
| <b># of Questions views:</b>                                                                                                                                                                                                                      | 1379                                      |
| <a href="https://www.dumpsfiles.com/files/Salesforce/OmniStudio-Developer/Salesforce.OmniStudio-Developer.v2026-01-02.q113">https://www.dumpsfiles.com/files/Salesforce/OmniStudio-Developer/Salesforce.OmniStudio-Developer.v2026-01-02.q113</a> |                                           |

### NEW QUESTION: 1

A developer creates an OmniScript to update billing information. After analyzing the different types of customer interactions that occur at the company, the developer determines updating billing information should be included in the majority of customer interactions, which are represented by more than 20 different FlexCards.

What is the most efficient way for the developer to configure the action that invokes the OmniScript?

- A. As an OS Action
- B. As a Custom Action
- C. As an OmniStudio Action
- D. As a Lightning Action

**Answer:** ([SHOW ANSWER](#))

Explanation

An OS Action is the most efficient way to configure the action that invokes the OmniScript, as it allows the developer to reuse the same OmniScript across multiple FlexCards without creating separate actions for each one. A Custom Action is used to invoke a custom Apex class or Lightning web component. An OmniStudio Action is used to invoke an Integration Procedure or a Calculation Procedure. A Lightning Action is used to invoke a Lightning component or a Visualforce page.

### NEW QUESTION: 2

Refer to the exhibit.

What JSON code correct represent the step in the OmniScript Structure panel shown?

- A)
- B)
- C)

D)

A. Option C

B. Option B

C. Option D

D. Option A

**Answer:** ([SHOW ANSWER](#))

### NEW QUESTION: 3

Refer to the exhibit below. In this integration production structure, what Send JSON Path would be used to send the Output of the Action1 element to a Remote Action?

A. Action1. BlockB. Block A

B. Action1: BlockB. Block A

C. BlockA: BlockB. Action 1

D. BlockB:BlockB. Action1

**Answer: B** ([LEAVE A REPLY](#))

Explanation

The correct syntax for the Send JSON Path is ActionName: BlockName, where ActionName is the name of the action element and BlockName is the name of the block element that contains the output data. The other options are either missing the colon or using incorrect names.

### NEW QUESTION: 4

Refer to the exhibit below. What JSON from the DRGetContactDetails action would display all six values correctly shown? BlkCases is a Repeat Block, and the names of the elements are the same as the label names without spaces.

A.

B.

C.

D.

**Answer: A** ([LEAVE A REPLY](#))

Explanation

According to the OmniScript Data JSON page, the OmniScript structure JSON defines the data elements and their properties that are used in an OmniScript. The exhibit shows an OmniScript structure JSON with six elements: ContactName, ContactPhone, ContactEmail, CaseNumber, CaseSubject, and CaseStatus. The DRGetContactDetails action is a DataRaptor Extract action that retrieves data from the Contact and Case objects in Salesforce. The BlkCases element is a Repeat Block that displays a list of cases related to the contact. Therefore, the JSON from the DRGetContactDetails action that would display all six values correctly shown is option A, which has the following structure:

The other options have different structures that do not match the OmniScript structure shown.

### NEW QUESTION: 5

Why would you clone an Integration Procedure instead of versioning it?

- A. The new Integration Procedure uses a Cache Block.
- B. The new Integration Procedure is replacing stub data.
- C. The new Integration Procedure is Chainable.
- D. The new Integration Procedure will be used independently.

**Answer: D** ([LEAVE A REPLY](#))

#### NEW QUESTION: 6

Refer to the exhibit.

The card layout uses an integration Procedure as a data source. The cards use the layout data source.

Which JSON data structure supports this card layout and follows best practices?

- A)
- B)
- C)

- A. Option B
- B. Option A
- C. Option C

**Answer: C** ([LEAVE A REPLY](#))

#### NEW QUESTION: 7

What is the reason for this? Refer to the exhibit below.

- A. Both parent and embedded OmniScripts have the same element name for the Set Values element.
- B. The WLC PubSub Messge flag in the Set Values action of the parent OmniScript has not been set.
- C. The flag passData.JSON in the parent OmniScript is not configured correctly.
- D. A developer failed to include a Navigate Action Element to pass data from the parent OmniScript.

**Answer: D** ([LEAVE A REPLY](#))

#### NEW QUESTION: 8

An OmniScript updates data from one Salesforce record, but when it completes, only some of the data is updated in Salesforce. A Data Mapper Load saves the data. What error could cause this behavior?

Choose 2 answers

- A. The Input JSON paths in the Data Mapper Load do not match the JSON sent from the OmniScript.
- B. The fields that are not updated are read-only in Salesforce.
- C. In the Data Mapper Load, in the preview tab, the RecordId is from the wrong record type.
- D. ContextId is misspelled in the merge code that passes the RecordId to the Data Mapper.

**Answer: (SHOW ANSWER)**

According to the Salesforce OmniStudio DataRaptor documentation, specifically under DataRaptor Load Best Practices and Common Issues:

- \* A. "The Input JSON paths in the Data Mapper Load do not match the JSON sent from the OmniScript." This is a common configuration issue. If the paths between the OmniScript's structure and the DataRaptor Load mapping are mismatched, fields may not map correctly, resulting in partial updates or no updates.
- \* B. "The fields that are not updated are read-only in Salesforce." If a field is Read-Only at the field-level security (FLS) or object schema, DataRaptor Load will not be able to write to it, which explains why only some data is updated.

Incorrect Options:

- \* C. The RecordId from the wrong record type would typically cause a complete failure, not a partial update.
- \* D. A misspelled ContextId could prevent data from being linked correctly, but this is less likely to cause partial field-level issues, and more likely to affect record association.

:

Salesforce OmniStudio Developer Guide # DataRaptor Load # Troubleshooting Salesforce Help Documentation: OmniStudio DataRaptor Best Practices

**NEW QUESTION: 9**

Refer to the exhibit.

A developer has configured an integration Procedure element with SEND/RESPONSE TRANSFORMATIONS as shown.

Alternatively, how could the developer configure Additional input to send exactly the same data? Assume that the developer checked Send Only Additional input.

- A)
- B)
- C)

- A. Option A
- B. Option C
- C. Option B

**Answer: B (LEAVE A REPLY)**

**NEW QUESTION: 10**

The OmniScript must retrieve device details stored in the Assetobject and then call an external system to send troubleshooting commands via REST API to the device.

Which two OmniScript element should the developer use to configure this functionality?

- A. DataRaptor Extract Action
- B. REST API Action
- C. Navigation Action
- D. SOQL Action

E. HTTP Action

**Answer: A,E ([LEAVE A REPLY](#))**

Explanation

According to the OmniScript Action Elements page, a DataRaptor Extract Action can be used to "get data from one or more Salesforce records" and an HTTP Action can be used to "get, save, or delete data through a web application programming interface (API)".

#### **NEW QUESTION: 11**

A developer needs to display the following information together on one FlexCard:

- \* Account name, address, phone number, website
- \* Primary contact first name, contact name, address, phone number, email

The account information must always be visible, and the contact information should only be visible as needed by the user.

What approach should the developer use to display the contact information on the card?

- A. Set the collapsible property on the block element
- B. Set the class "collapsible" on the block element
- C. Use a Datatable element
- D. Use a conditional FlexCard State

**Answer: A ([LEAVE A REPLY](#))**

#### **NEW QUESTION: 12**

Refer to the exhibit below. In this Integration Procedure structure, what Send JSON Path would you use to send the output of the ActionZ element to a Response Action?

- A. BlockX:BlockY:ActionAZ
- B. ActionZ:BlockY:BlockX
- C. BlockX.BlockYActionZ
- D. ActionZ:BlockY:BlockX

**Answer: A ([LEAVE A REPLY](#))**

#### **NEW QUESTION: 13**

A developer is troubleshooting an Integration Procedure with two elements: A Remote Action named FetchCart and a Response Action named ResponseCart.

In Preview, what JSON node shows the data sent to the Response Action?

- A. ResponseCartDebug
- B. ResponseCart
- C. FetchCart
- D. Response

**Answer: A ([LEAVE A REPLY](#))**

#### **NEW QUESTION: 14**

Refer to the exhibit.

A developer creates an OmniScript display FirstName, LastName, and BirthDate of a contact using a Type Ahead Block. The DataRaptor used in the Type Ahead has been tested and fetches the correct data.

When previewing Omniscript, the developer enters a name in the Type Ahead and makes a selection of a contact from the list. However, the text fields FirstName, LastName, and BirthDate are not getting populated with the data.

What is the reason that the fields fail to display the fetched data?

- A. Lookup Mode is not selected in the properties of the Type Ahead Block.
- B. Use Data JSON is not selected in the properties of the Type Ahead Block.
- C. FirstName, LastName, and Birthdate are not placed inside the Type ahead Block.
- D. The Typeahead key is not in the correct format

**Answer:** ([SHOW ANSWER](#))

Explanation

The FirstName, LastName, and BirthDate fields should be placed inside the Type Ahead Block, so that they can receive the data from the selected record in the Type Ahead list. The Type Ahead Block has a Data JSON Path property that specifies the path to the data node that contains the record fields. For example, if the Data JSON Path is set to Contact, then the FirstName field should have a Value property set to `{{Contact.FirstName}}`.

#### NEW QUESTION: 15

A developer needs to configure a DataRaptor to retrieve data from a single object. The structure of the output data does not need to be changed.

Following best practices, which type of DataRaptor should the developer use?

- A. DataRaptor Transform
- B. DataRaptor Extract
- C. DataRaptor Load
- D. DataRaptor Turbo Extract

**Answer:** ([SHOW ANSWER](#))

A DataRaptor Turbo Extract is a simplified version of a DataRaptor Extract that can retrieve data from a single object without changing the structure of the output data. It is suitable for this scenario because the developer does not need to transform or load the data

#### NEW QUESTION: 16

On a FlexCard canvas, several fields display with Salesforce data, but one of the fields shows only the label.

What could cause this?

- A. In the Setup Panel, {recordId} is misspelled in the Data Source Input Map.
- B. The field name in the FlexCard state does not match the DataRaptorExtract's Output JSON Path name.

C. In the FlexCard state, the Field type for the field does not match the type in the Salesforce record.

D. There are No test Data test Parameters configured.

**Answer: B (LEAVE A REPLY)**

According to the FlexCard Designer Overview page, one possible cause of a field showing only the label is that "the field name in the FlexCard state does not match the DataRaptor Extract's Output JSON Path name".

**Valid OmniStudio-Developer Dumps** shared by TrainingDump.com for Helping Passing OmniStudio-Developer Exam! TrainingDump.com now offer the **newest OmniStudio-Developer exam dumps**, the TrainingDump.com OmniStudio-Developer exam **questions have been updated** and **answers have been corrected** get the **newest** TrainingDump.com OmniStudio-Developer dumps with Test Engine here:

<https://www.trainingdump.com/Salesforce/OmniStudio-Developer-practice-exam-dumps.html>

(107 Q&As Dumps, **40%OFF** Special Discount: **Exam-Tests**)

#### NEW QUESTION: 17

Refer to the exhibit below. A developer has configured an integration Procedure element with Additional input.

Alternatively, how could the developer configure SEND/RESPONSE TRANSFORMATION to send exactly the same data? Assume the developer has un-checked Send Only Additional input.

A.

B.

C.

D.

**Answer: (SHOW ANSWER)**

The Send JSON Path syntax for accessing an element from an Integration Procedure structure is BlockName.

ElementName. In this case, the BlockName is BlockX and the ElementName is ActionZ. The colon (:) is used to separate the input and output parameters, not the block and element names. The order of the block and element names should follow the hierarchy of the structure, from top to bottom. The Additional input parameter is not needed in this case, as it is already included in the Send JSON Path.

#### NEW QUESTION: 18

A developer needs to retrieve data from an external system that stores policy data. The external system supports REST APIs to access and update the policies. Due to the volume of the policy data and peak hours of business, calls to the REST APIs sometimes take longer than expected to response.

The developer creates an Integration Procedure to retrieve the policy data for use in an OmniScript.

Given the external system's known performance issues, which configuration should be used to implement the call to the external system?

Choose 2 answers

- A. Check the Chain on Step Check on the HTTP Action in the Integration Procedure
- B. Set the Timeout property on the HTTP Action in the Integration Procedure
- C. Check the Chainable checkbox on the integration procedure Action in the OmniScript
- D. Configure a Remote action with timeout settings of 120000

**Answer: A,D ([LEAVE A REPLY](#))**

#### NEW QUESTION: 19

A customer has a new Engagement Manager who is going to be the new Primary Contact for the Account.

What type of mapping does a DataRaptor Load use to create the new contact and then add it as the new Primary Contact?

- A. Relationship Query
- B. Linked Mapping
- C. Lookup Mapping
- D. Lookup Key

**Answer: ([SHOW ANSWER](#))**

According to the DataRaptor Load Overview page, a Linked Mapping is used to "create or update multiple records in different objects that are related by lookup fields".

#### NEW QUESTION: 20

A developer needs to transform contact data into a JSON array.

Given the input JSON shown above, what are two ways a developer could configure a DataRaptor transform to achieve the expected Output JSON? Choose 2 answers

- A. Use a formula LIST(Contact), and add the output of the formula as the input in the Transform tab.
- B. Set the Input JSON path as List(Contact) and the Output JSON Path as Contact.
- C. Set the Input JSON Path as Contact the Output JSON Path as Contact and the output Data type as List.
- D. Set the input JSON Path as Contact and the Output JSON Path as List (Contact)

**Answer: A,C ([LEAVE A REPLY](#))**

A DataRaptor Transform can be used to transform data from one format to another, such as JSON, XML, or CSV. The developer can specify the input and output paths for each field in the Transform tab. The developer can also use formulas to manipulate data in the Formula tab. To transform contact data into a JSON array, the developer can use either of these methods:

\* Use a formula LIST(Contact), and add the output of the formula as the input in the Transform tab. This will create a list of contact objects from the input JSON and output it as a JSON array.



\* Set the Input JSON Path as Contact, the Output JSON Path as Contact, and the Output Data Type as List. This will output each contact object as an element of a JSON array.

#### NEW QUESTION: 21

in a DataRaptor Extract JSON Path, which option below has the correct syntax for a relationship query for a native Salesforce record?

- A. Contact: Caseld:Subject
- B. Contact:Caseld\_\_rSubject
- C. Contact:Caseld\_\_r-Subject
- D. ContactCaseld. Subject

**Answer: C** ([LEAVE A REPLY](#))

#### NEW QUESTION: 22

..... configure Additional input to send exactly the same data? Assume that the develop checked Send Only Additional input.

- A.
- B.
- C.
- D.

**Answer: (**[SHOW ANSWER](#)**)**

Explanation

Option D is the correct way to configure Additional input to send exactly the same data as Input Data. The Additional input should have the same key/value pairs as Input Data, and the value should be set to

{{InputData.key}} for each key. This will pass the value of Input Data for each key to Additional input.

#### NEW QUESTION: 23

You want to send all data from a FlexCard's data source to a Datatable in a child FlexCard. What is the variable you put in the Data Node field in the parent FlexCard that gets all the records?

- A. {recordid}
- B. {records}
- C. {records [0]}
- D. {Parent.id}

**Answer: (**[SHOW ANSWER](#)**)**

#### NEW QUESTION: 24

A developer is creating an OmniScript that Provisions trial orgs to their customers. The following text block in the OmniScript uses a merge code to display the ID for the new trial org:

Welcome to Salesforce

Your ID is %Details: Customer10:ID%

During testing, the developer notices that the ID does not display. The data JSON is structured as shown below.

How should the developer correct the merge code in order for the ID to display?

- A. To %%Details:Customer|0:ID%%
- B. To %%Details:Customer|n:ID%
- C. To %%Details:Customer|1:ID%
- D. To \$Details:Customer|0:ID\$

**Answer: C** ([LEAVE A REPLY](#))

The merge code syntax for accessing an array element is %%Details:Customer|1:ID%%, where 1 is the index of the element. The index starts from 1, not 0, so the first element is Customer|1. The % sign is used for single-value merge codes, not array merge codes. The \$ sign is used for variables, not merge codes.

#### NEW QUESTION: 25

What OmniStudio tool pre-populates the data in a PDF used by an OmniScript?

- A. A DataRaptor Transform
- B. A DataRaptor Extract
- C. A SOQL Query
- D. A DataRaptor Load

**Answer:** ([SHOW ANSWER](#))

#### NEW QUESTION: 26

What OmniStudio tool pre-populates the data in a PDF used by an OmniScript?

- A. A SOQL Query
- B. A DataRaptor Load
- C. A DataRaptor Extract
- D. A DataRaptor Transform

**Answer: D** ([LEAVE A REPLY](#))

Explanation

According to the DataRaptor Transform Overview page, a DataRaptor Transform can be used to "pre-populate data in PDFs used by OmniScripts".

#### NEW QUESTION: 27

A developer has a requirement to create a child FlexCard that contains all of its parent FlexCard's records in a Data Table. How should the developer configure the parent FlexCard's Node?

- A. {Records {0}}
- B. {Records}
- C. {Params, records}
- D. {Recorded}

**Answer: B** ([LEAVE A REPLY](#))

The Node field for the parent FlexCard should be set to {Records}, which is an array of all the records retrieved by the parent FlexCard data source. This will allow the child FlexCard to access the records and display them in a DataTable.

#### **NEW QUESTION: 28**

A developer needs to create a list of cases for an account in a single Datable in a FlexCard. Like the one shown below.

How can the developer configure the FlexCard to display the case records in this way?

- A.** Enable the Repeat Records feature on the FlexCard Setup tab
- B.** Select the Repeatable Mode property on the data table elements
- C.** Enable the record Looping feature on the data table elements
- D.** Disable the Repeat Record feature on the FlexCard setup tab

**Answer: D** ([LEAVE A REPLY](#))

#### **NEW QUESTION: 29**

A developer needs to change some field labels on a FlexCard. The FlexCard is currently deployed to production. The developer that the best course of action is to version the FlexCard rather than cloning it.

Which factor would lead the developer to this decision?

- A.** The new and current versions will be displayed together on the same target.
- B.** Another team member is developing new action, fields and styling for the current version of the FlexCard.
- C.** All instance of the FlexCard must be updated with the changes.
- D.** The new version of the FlexCard will be used in a new Console, and the current version of the FlexCard should remain unchanged.

**Answer: D** ([LEAVE A REPLY](#))

#### **NEW QUESTION: 30**

Refer to the exhibit.

A developer has configured an integration Procedure element with SEND/RESPONSE TRANSFORMATIONS as shown.

Alternatively, how could the developer configure Additional input to send exactly the same data?

Assume that the developer checked Send Only Additional input.

- A.**
- B.**
- C.**

**Answer: C** ([LEAVE A REPLY](#))

Option C is the correct way to configure Additional input to send exactly the same data as Input Data. The Additional input should have a key/value pair for each field in Input Data, and the value should be set to

{{InputData.field}} for each field. This will pass the value of Input Data for each field to Additional input.

#### NEW QUESTION: 31

A developer is creating an OmniScript that provisions trail orgs to their customers. The following text block in the Omniscript uses a merge code to display the ID for the new trail org:

- A. To %Details: Customer|1: ID%
- B. To %sDetails: Customer|0: ID\$
- C. To %Details: Customer|n: ID%
- D. To %%%sDetails: Customer|0: ID%%%

Answer: ([SHOW ANSWER](#))

**Valid OmniStudio-Developer Dumps** shared by TrainingDump.com for Helping Passing OmniStudio-Developer Exam! TrainingDump.com now offer the **newest OmniStudio-Developer exam dumps**, the TrainingDump.com OmniStudio-Developer exam **questions have been updated** and **answers have been corrected** get the **newest** TrainingDump.com OmniStudio-Developer dumps with Test Engine here:

<https://www.trainingdump.com/Salesforce/OmniStudio-Developer-practice-exam-dumps.html>

(107 Q&As Dumps, **40%OFF** Special Discount: **Exam-Tests**)

#### NEW QUESTION: 32

A developer has a requirement to create a child FlexCard that contain all of its parent FlexCard's records in a Datatable.

- A. {Records[0]}
- B. {Records}
- C. {Params records}
- D. {recordId}

Answer: B ([LEAVE A REPLY](#))

Explanation

The correct syntax for passing all of the parent FlexCard's records to a child FlexCard is {Records}, which represents an array of records. The other options are incorrect because they either use an invalid syntax or refer to a single record instead of an array of records.

#### NEW QUESTION: 33

Which calculation procedure version in the list would execute on 2/15/2020at 12:00 PM?

- A. Version Number 1
- B. Version Number 4
- C. Version Number 2
- D. Version Number 3

**Answer: B** ([LEAVE A REPLY](#))

the calculation procedure version that would execute on 2/15/2020 at 12:00 PM is the one that has the start date time and end date time that include that date and time, and also has the highest priority among the enabled versions. In this case, only version number 4 meets these criteria, as it has a start date time of 2/1

/2020 12:00 AM, an end date time of 4/1/2020 12:00 AM, a priority of 1, and is enabled. The other versions either have a different start or end date time, a lower priority, or are not enabled.

#### **NEW QUESTION: 34**

An integration Procedure uses an HTTP action to make a REST API call. The response from the REST API must be converted into a specific XML structure before sending it as an input to another external web service.

How should the developer configure the Integration Procedure to meet this requirement?

- A. Use a Remote Action that calls the XMLStreamReader class
- B. Use a Remote Action that calls the XMLStreamWriter class
- C. Use a DataRaptor Transform to convert JSON to XML
- D. Use a DataRaptor Extract and check the XML checkbox on the Output JSON Path.

**Answer:** ([SHOW ANSWER](#))

According to the OmniStudio Developer Guide, "DataRaptor Transform actions can convert JSON to XML and vice versa." Therefore, the correct answer is C.

#### **NEW QUESTION: 35**

Which property enables custom Lightning web components to override an individual OmniScript element's component?

- A. HTML Template ID
- B. LWC Component Override
- C. Element Type to LWC Component Mapping
- D. Enable LWC

**Answer:** ([SHOW ANSWER](#))

#### **NEW QUESTION: 36**

A developer creates a new FlexCard to display customer data and actions, such as updating billing information and changing the contact for the customer account. The FlexCard contains 10 fields and 5 actions.

During testing, several fields display with the correct data, but one of the fields shows only the label.

What could cause this?

- A. The fields have exceeded the maximum number allowed on the card.
- B. The field is null in the Salesforce record.
- C. {recordId} is misspelled in the Data Source Input Map.
- D. There are no test parameters configured.

**Answer: (SHOW ANSWER)**

According to the FlexCard Designer Overview page, another possible cause of a field showing only the label is that "the field is null on the Salesforce record".

**NEW QUESTION: 37**

Refer to the exhibit below. In this integration production structure, what Send JSON Path would be used to send the Output of the Action1 element to a Remote Action?

- A. Action1. BlockB. Block A
- B. Action1: BlockB. Block A
- C. BlockA: BlockB. Action 1
- D. BlockB:BlockB. Action1

**Answer: (SHOW ANSWER)**

The correct syntax for the Send JSON Path is ActionName: BlockName, where ActionName is the name of the action element and BlockName is the name of the block element that contains the output data. The other options are either missing the colon or using incorrect names.

**NEW QUESTION: 38**

An integration Procedure uses an HTTP action to make a REST API call. The response from the REST API must be converted into a specific XML structure before sending it as an input to another external web service.

How should the developer configure the Integration Procedure to meet this requirement?

- A. Use a DataRaptor Extract and check the XML checkbox on the Output JSON Path.
- B. Use a DataRaptor Transform to convert JSON to XML
- C. Use a Remote Action that calls the XMLStreamWriter class
- D. Use a Remote Action that calls the XMLStreamReader class

**Answer: B (LEAVE A REPLY)**

**NEW QUESTION: 39**

A developer has an existing DataRaptor Load that insert Contact records with inputs as LastName and firstName. The DataRaptor works as expected when previewed.

The developer creates an integration Procedure to test the DataRaptor and is using a SetValues element in the Integration Procedure to set the first name and last name for the contact record.

The DataRaptor and Integration Procedure are set up as shown in the exhibit below.

When the developer executes the Integration procedure in preview, the following error message displays: Required fields are missing: [last Name]", How should the developer address this issue?

- A. The DataRaptor Post Action in the integration procedure should have been executed before the Set Values Action
- B. The Set values Action Keys should include the DataRaptor Post Action element name path, e.g LoadContactDetails, lastname
- C. The valid field names should be added in the Domain object field in the DataRaptor

**D.** SetValueContactDetails should have been added to Additional input of DataRaptor Post Action in Integration Procedure

**Answer: D** ([LEAVE A REPLY](#))

#### **NEW QUESTION: 40**

In an OmnoScript, a developer needs to configure a Disclosure element to require user input only if the user already checked a Non-Disclosure Agreement Checkbox.

How should the developer configure the conditional view to meet this requirement?

- A.** Disable read only if true
- B.** Set element to optional if false
- C.** Show element if true
- D.** Set element to require if true

**Answer: C** ([LEAVE A REPLY](#))

#### **NEW QUESTION: 41**

A developer configure a Flexcard with a DataRaptor data source that uses the params.id as an. When the developer clicks Views Data on the FlexCard, valid data displays. However, when the developer previews the layout, the FlexCard does not display. What could cause this error?

Choose 2 answers

- A.** The Data Node field for the FlexCard is empty.
- B.** The RecordId in the Test Data Source settings ins for the wrong record type.
- C.** The attribute haven't been configured to pass the data to the fields.
- D.** There is not Salesforce record for the FlexCard based on the RecordId in the layout's Test Data Source Settings.

**Answer: B,C** ([LEAVE A REPLY](#))

#### **NEW QUESTION: 42**

Which calculation procedure version in the list would execute on 2/15/2020 at 12:00 PM?

- A.** Version Number 2
- B.** Version Number 1
- C.** Version Number 4
- D.** Version Number 3

**Answer:** ([SHOW ANSWER](#))

#### **NEW QUESTION: 43**

Refer to the exhibit below. In this integration production structure, what Send JSON Path would be used to send the Output of the Action1 element to a Remote Action?

- A.** BlockB: BlockB. Action1
- B.** Action1: BlockB. Block A
- C.** Action1. BlockB. Block A
- D.** BlockA: BlockB. Action 1

**Answer:** ([SHOW ANSWER](#))

**NEW QUESTION: 44**

Refer to the exhibit.

A developer has configured an integration Procedure element with SEND/RESPONSE TRANSFORMATIONS as shown.

Alternatively, how could the developer configure Additional input to send exactly the same data? Assume that the developer checked Send Only Additional input.

**A.**

**B.**

**C.**

**Answer: C** ([LEAVE A REPLY](#))

Option C is the correct way to configure Additional input to send exactly the same data as Input Data. The Additional input should have a key/value pair for each field in Input Data, and the value should be set to

{{InputData.field}} for each field. This will pass the value of Input Data for each field to Additional input.

**NEW QUESTION: 45**

Refer to the exhibit.

All inputs to the Calculation Matrix are set correctly.

The Calculation Matrix has the following input:

What is the output?

**A.** 13.99

**B.** 12.99

**C.** 12.99,13.99

**D.** Null

**Answer: A** ([LEAVE A REPLY](#))

**NEW QUESTION: 46**

In a Calculation Procedure, what is required for the output of a Calculation Step to be used in an Aggregation Step?

**A.** It must be included in the calculation output

**B.** It must be a calculation step

**C.** It must be included in constants

**D.** It must be a matrix lookup step

**Answer:** ([SHOW ANSWER](#))



**Valid OmniStudio-Developer Dumps** shared by TrainingDump.com for Helping Passing OmniStudio-Developer Exam! TrainingDump.com now offer the **newest OmniStudio-Developer exam dumps**, the TrainingDump.com OmniStudio-Developer exam **questions have been updated** and **answers have been corrected** get the **newest** TrainingDump.com OmniStudio-Developer dumps with Test Engine here:

<https://www.trainingdump.com/Salesforce/OmniStudio-Developer-practice-exam-dumps.html>

(107 Q&As Dumps, **40%OFF** Special Discount: **Exam-Tests**)

#### NEW QUESTION: 47

Refer to the exhibit below. What JSON from the DRGetContactDetails action would display all six values correctly in the shown? BlkCases is a Repeat Block, and the names of the elements are the same as the label names without spaces.

- A)
- B)
- C)
- D)

- A. Option C
- B. Option A
- C. Option D
- D. Option B

**Answer: B** ([LEAVE A REPLY](#))

#### NEW QUESTION: 48

A developer has an existing DataRaptorLoad that insert Contact records with inputs as LastName and firstName. The DataRaptor works as expected when previewed.

The developer creates an integration Procedure to test the DataRaptor and is using a SetValues element in the Integration Procedure to set the first name and last name for the contact record.

The DataRaptor and Integration Procedure are set up as shown in the exhibit below.

When the developer executes the Integration procedure in preview, the following error message displays:

Required fields are missing: [last Name]",

How should the developer address this issue?

- A. SetValuesContactDetails should have been added to Additional input of DataRaptor Post Action in Integration Procedure
- B. The Set values Action Keys should include the DataRaptor Post Action element name path, e.g LoadContactDetails, lastname
- C. The DataRaptor Post Action in the integration procedure should have been executed before the Set Values Action
- D. The valid field names should be added in the Domain object field in theDataRaptor

**Answer: A** ([LEAVE A REPLY](#))

According to the Integration Procedure Actions page, "To pass data from a Set Values action to a DataRaptor action, add the Set Values action name to the Additional Input field of the DataRaptor action."

#### **NEW QUESTION: 49**

You have configured an Integration Procedure element with SEND/RESPONSE TRANSFORMATIONS as shown.

Alternatively, how would you configure Additional Input to send exactly the same data? Assume that you check Send Only Additional Input.

- A)
- B)
- C)
- D)

- A. OptionD
- B. OptionB
- C. OptionA
- D. OptionC

**Answer: A** ([LEAVE A REPLY](#))

#### **NEW QUESTION: 50**

A customer sets up to LWC Omniscripts, one embedded into another. Account is set in a Set Values element in the parent Omniscript.

The AccountId set in the parent Omniscript is used to another Set Values element ContextAccountId in the embedded OmniScript. The embedded Omniscript is activated.

While previewing the OmniScript flow from the parent, it is found that Account is set correctly in the parent OmniScript. However. ContextAccountId in the embedded OmniScript is not set with the AccountId from parent Omniscript. On previewing the embedded OmniScript individually, it is found that ContextAccountId is set correctly.

What is the reason for this? Refer to the exhibit below.

- A. Both parent and embedded OmniScripts have the same element name for the Set values element.
- B. A developer failed to include a Navigation Element to pass data from the parent OmniScript.
- C. The LWC PubSub Message flag in the Set Values action of the parent has not been set.
- D. The flag pass Data JSON in the parent OmniScript in not configured correctly.

**Answer: B** ([LEAVE A REPLY](#))

The LWC PubSub Message flag in the Set Values action of the parent OmniScript enables the parent OmniScript to send data to the embedded OmniScript using a custom event. If this flag is not set, the data will not be passed to the embedded OmniScript.

#### **NEW QUESTION: 51**

Which two in an integration Procedure or DataRaptor can execute a function like CONCAT or DATEDIFF?

Choose 2 answers

- A. In a Set Values Action in a Value field.
- B. In a DataRaptor in an Output TabOutput JSON Path.
- C. In a DataRaptor Action in an Input Parameters value field.
- D. In a Remote Action in an Additional Output value field.

**Answer: A,D (LEAVE A REPLY)**

A Set Values Action in a Value field and a Remote Action in an Additional Output value field can execute a function like CONCAT or DATEDIFF by using the syntax `{{function(parameters)}}`. For example, `{{CONCAT('Hello', 'World')}}` or `{{DATEDIFF('2021-01-01', '2021-01-31')}}`.

### NEW QUESTION: 52

A developer creates a new FlexCard to display customer data and actions, such as updating billing information and changing the contact for the customer account. The FlexCard contains 10 fields and 5 actions.

During testing, several fields display with the correct data, but one of the fields shows only the label.

What could cause this?

- A. The fields have exceeded the maximum number allowed on the card.
- B. The field is null on the Salesforce record.
- C. `{recordId}` is misspelled in the Data Source Input Map.
- D. There are no test parameters configured.

**Answer: B (LEAVE A REPLY)**

Explanation

According to the FlexCard Designer Overview page, another possible cause of a field showing only the label is that "the field is null on the Salesforce record".

### NEW QUESTION: 53

While using the Lightning App Builder, you add a Custom Component to the console, but the component you want to add does not appear in the dropdown list.

What could cause this?

- A. The FlexCard has a recordId that is for the wrong record type.
- B. The data source for the FlexCard is not active.
- C. The record displayed in the Lightning App Builder preview has no data for the record displayed.
- D. The FlexCard does not have an active version.

**Answer: D (LEAVE A REPLY)**

### NEW QUESTION: 54

Refer to the exhibit.

What JSON code correct represent the step in the OmniScript Structure panel shown?

- A.
- B.
- C.
- D.

**Answer:** ([SHOW ANSWER](#))

According to the OmniScript Data JSON page, the OmniScript structure JSON defines the data elements and their properties that are used in an OmniScript. The exhibit shows an OmniScript structure JSON with three elements: Step, Block, and Telephone. The Step element is an empty object, the Block element is an object with two properties: Text and Telephone, and the Telephone element is a string. Therefore, the JSON code that correctly represents the step in the OmniScript Structure panel shown is option C, which has the following structure:

The other options have different structures that do not match the OmniScript structure shown. Therefore, the correct answer is C.

#### NEW QUESTION: 55

A developer writes an OmniScript that includes a DataRaptor that updates the Account status based on information provided from the OmniScript. The information must be updated only if the Account record already exists. Otherwise, a new account must be created.

How should the developer accomplish this task?

- A. Check the Upsert Key checkbox on the Account Status field
- B. Check the Upsert Key and Is Required for Upsert checkboxes on the Account Id field
- C. Populate the Lookup Object and Lookup Fields
- D. Check Overwrite Target for All Null Inputs checkbox on the Account Id field

**Answer:** ([SHOW ANSWER](#))

The Upsert Key checkbox indicates that the field is used as a key for upserting records. The Is Required for Upsert checkbox indicates that the field is mandatory for upserting records. The developer needs to check both checkboxes on the Account Id field to update the Account status only if the Account record already exists. Otherwise, a new account will be created.

#### NEW QUESTION: 56

A developer needs to build a multi-step intake form. Each step must allow the user to cancel the intake at any time. The developer is using an LWC OmniScript to build the form.

How should the developer implement thecancel functionality for all steps using the LWC OmniScript Designer?

- A. Check the Enable Cancel checkbox in the Setup tab under Cancel Options.
- B. Add a navigation Action inside each step and set the Component name to "Cancel",
- C. Add a navigation Action outside each step and set the Element Name to "Cancel",
- D. Add a navigation Action inside each step and set the Element Name to "Cancel",

**Answer:** A ([LEAVE A REPLY](#))

### Explanation

Checking the Enable Cancel checkbox in the Setup tab under Cancel Options allows the developer to enable the cancel functionality for all steps in the OmniScript. The user can cancel the OmniScript at any time by clicking the Cancel button in the top right corner of the OmniScript. Adding a navigation Action inside each step is not necessary and would clutter the OmniScript design. Setting the Component name or Element Name to "Cancel" has no effect on enabling the cancel functionality.

### NEW QUESTION: 57

A developer has a requirement to create a child FlexCard that contain all of its parent FlexCard's records in a Datatable.

- A. {Params records}
- B. {recordId}
- C. {Records[0]}
- D. {Records}

**Answer:** ([SHOW ANSWER](#))

The correct syntax for passing all of the parent FlexCard's records to a child FlexCard is {Records}, which represents an array of records. The other options are incorrect because they either use an invalid syntax or refer to a single record instead of an array of records.

### NEW QUESTION: 58

A developer needs to display read-only contact information in a OmniScript. The developer will format the information as a table, using merge codes to dynamically include first name, last name, street address, state, postal, code, and country from the data JSON.

Which OmniScript element should the developer use to meet this requirement?

- A. Rich text Area
- B. Text area
- C. Text Block
- D. Edit Block

**Answer:** C ([LEAVE A REPLY](#))

### Explanation

A Text Block element allows the developer to display read-only text in a table format, using merge codes to dynamically include data from the data JSON. A Rich Text Area element is used to display formatted text with images and links. A Text Area element is used to display editable text in a single line or multiple lines. An Edit Block element is used to display editable fields in a form layout.

### NEW QUESTION: 59

- A)
- B)
- A. Option A

B. Option B

Answer: ([SHOW ANSWER](#))

#### NEW QUESTION: 60

A developer is configuring a DataRaptor Load to Savecontract data. The developer needs to set the record type of the contact using DeveloperName.

Which two configuration actions should the developer take to set this up in the DataRaptor Load?

- A. Check is Lookup property when mapping the fields.
- B. AddLink toRecordType object in the Contact Object with the id field of RecordType object.
- C. Select RecordType in the Lookup object list. Development in the lookup Field list, and ID in the Lookup Requested Field list.
- D. Select RecordType in the Lookup Object list. ID in the Lookup Field list, and Development in the Lookup requested Field list.

Answer: A,C ([LEAVE A REPLY](#))

Explanation

A Set Values Action in a Value field and a Remote Action in an Additional Output value field can execute a function like CONCAT or DATEDIFF by using the syntax {{function(parameters)}}. For example,

{{CONCAT('Hello', 'World')}} or {{DATEDIFF('2021-01-01', '2021-01-31')}}.

#### NEW QUESTION: 61

A developer is building a DataRaptor Load for an Integrate Procedure used in an OmniScript.

Based on best practices, how should the developer configure the Input JSON?

- A. Build the Input JSON node by node in the DataRaptor Designer.
- B. Copy the Input JSON from the OmniScript {Data} modal.
- C. Copy the Input JSON from the DataRaptor Action Debug node.
- D. Build the Input JSON node by node in an editor.

Answer: B ([LEAVE A REPLY](#))

**Valid OmniStudio-Developer Dumps** shared by TrainingDump.com for Helping Passing OmniStudio-Developer Exam! TrainingDump.com now offer the **newest OmniStudio-Developer exam dumps**, the TrainingDump.com OmniStudio-Developer exam **questions have been updated** and **answers have been corrected** get the **newest** TrainingDump.com OmniStudio-Developer dumps with Test Engine here:

<https://www.trainingdump.com/Salesforce/OmniStudio-Developer-practice-exam-dumps.html>

(107 Q&As Dumps, **40%OFF** Special Discount: **Exam-Tests**)

#### NEW QUESTION: 62

Which three are true about Calculation Matrix inputs? Choose 3 answers

- A. They must contain numerical data.
- B. They can represent ranges.
- C. They can be a combination of values.
- D. They must be unique.

**Answer:** ([SHOW ANSWER](#))

#### **NEW QUESTION: 63**

A developer creates an OmniScript to update billing information. After analyzing the different types of customer interactions that occur at the company, the developer determines updating billing information should be included in the majority of customer interactions.

What should the developer use to configure the action that invokes the OmniScript?

- A. OmniScript Action
- B. Custom Action
- C. Lightning Action

**Answer: A** ([LEAVE A REPLY](#))

From OmniStudio Best Practices for Modular Script Design, OmniScript Actions are the preferred mechanism to invoke another OmniScript within a parent OmniScript. This approach enables reusability and modularization, especially when a function (like updating billing information) is common across many interactions.

\* A. OmniScript Action - This is the correct and standard method for embedding or launching one OmniScript from another. It allows developers to reuse common scripts without duplicating logic.

Incorrect Options:

\* B. Custom Action requires custom Apex or LWC development, which is unnecessary for this use case.

\* C. Lightning Action is typically used to invoke OmniScripts from Lightning pages, not within OmniScripts themselves.

:

OmniStudio Developer Guide # OmniScript Actions

#### **NEW QUESTION: 64**

In a calculation procedure, what is required for the output of a calculation step to be used in an aggregation step?

- A. It must be a calculation step.
- B. It must be a matrix lookup step.
- C. It must be included in the calculation output.
- D. It must be included in constants.

**Answer: C** ([LEAVE A REPLY](#))

#### **NEW QUESTION: 65**

What JSON code correctly represents the step in the OmniScript Structure panel shown?

- A. "Step1": {"Block1": {"Text1": "Text" }, "Block2": {"Telephone 1": "1234567890", "Checkbox1": false, "Block3": { "Multi-select1": "Value A;Value B" }}}}
- B. "Step1": { "Block1": { "Text1" "Text", "Telephane1": "1234567890" }. "Block2": { "Checkbox1" false, "Block3": { "Multi-selecti": "Value Value A:Value B A;value B" }}}}
- C. "Step1": {"Block1": { "Text1": "Text", "Telephone 1": "1234567890", "Block2": { "Checkbox1": false }, "Block3": { "Multi-select1": "Value A;Value B"}}} Written
- D. "Step1": {"Block1": { "Text1": "Text". "Block2": { "Telephone1": "1234567890", "Checkbox1": false }, "Block": { "Multi-selecti": "Value A;Value B" }}}

**Answer:** [\(SHOW ANSWER\)](#)

#### NEW QUESTION: 66

A developer creates an OmniScript to update billing information. After analyzing the different types of customer interactions that occur at the company, the developer determines updating billing information should be included in the majority of customer interactions, which are represented by more than 20 different FlexCards.

What is the most efficient way for the developer to configure the action that invokes the OmniScript?

- A. As an OmniStudio Action
- B. As a Lightning Action
- C. As a Custom Action
- D. As an OS Action

**Answer:** A [\(LEAVE A REPLY\)](#)

#### NEW QUESTION: 67

A developer needs to build a DataRaptor Transform to send current weather to both an OmniScript Card Layout. Which of these samples would be valid for the Expected Output JSON?

- A.
- B.
- C.
- D.

**Answer:** D [\(LEAVE A REPLY\)](#)

According to the Transform External Data Unit, the Expected Output JSON should match the Output Path of the DataRaptor Transform. In option D, the Output Path is Current:CityState, which matches the Expected Output JSON. The other options have different Output Paths that do not match the Expected Output JSON.

Therefore, the correct answer is D.

#### NEW QUESTION: 68

A developer needs to retrieve data from an external system that stores policy dat



a. The external system supports REST APIs to access and update the policies. Due to the volume of the policy data and peak hours of hours of business, calls to the REST APIs sometimes take longer than expected to response.

The developer creates an Integration Procedure to retrieve the policy data for use in an OmniScript.

Given the external system's known performance issues, which configuration should be used to implement the call to the external system?

Choose 2 answers

- A. Configure a Remote action with timeout settings of 120000
- B. Check the Chainable checkbox on the integration procedure Action in the OmniScript
- C. Set the Timeout property on the HTTP Action in the Integration Procedure
- D. Check the Chain on Step Check on the HTTP Action in the Integration Procedure

**Answer: A,D** ([LEAVE A REPLY](#))

#### NEW QUESTION: 69

You have so many fields on a FlexCard that it looks cluttered. Based on best practices, what is the most efficient way to declutter it?

- A. Use a flyout action
- B. Use a datatable or chart element
- C. Delete some of the actions
- D. Use a child FlexCard

**Answer: A** ([LEAVE A REPLY](#))

#### NEW QUESTION: 70

Refer to the exhibit below. A developer has configured an integration Procedure element with Additional input.

Alternatively, how could the developer configure SEND/RESPONSE TRANSFORMATION to send exactly the same data? Assume the developer has un-checked Send Only Additional input.

- A.
- B.
- C.
- D.

**Answer: A** ([LEAVE A REPLY](#))

#### NEW QUESTION: 71

When launching an OmniScript from an action on a FlexCard, the OmniScript displays, but no Salesforce data is populated:

Which two errors could cause this behavior?

Choose 2 answers

Choose 2 answers

- A. The Id Field for Actions in the FlexCard is blank.

- B. There is no active version of the Data Raptor Extract.
- C. There is no active version of the OmniScript
- D. In the DataRaptor Extract Action, the Input Parameters Filter Value is misspelled.

**Answer: A,D** ([LEAVE A REPLY](#))

Explanation

The Id Field for Actions in the FlexCard specifies which field from the FlexCard data source will be used as the record ID for the OmniScript. If this field is blank, the OmniScript will not receive any record ID and will not be able to retrieve any Salesforce data. In the DataRaptor Extract Action, the Input Parameters Filter Value determines how to filter the data based on the record ID. If this value is misspelled, the DataRaptor Extract will not be able to match the record ID and will not return any data.

#### NEW QUESTION: 72

What parent JSON node name must be sent to a Calculation Procedure?

- A. Input
- B. Inputs
- C. input
- D. inputs

**Answer: D** ([LEAVE A REPLY](#))

#### NEW QUESTION: 73

How is data accessed for a Field element in a FlexCard that wants the AccountName?

- A. {AccountName}
- B. records
- C. AccountName
- D. {records}

**Answer:** ([SHOW ANSWER](#))

#### NEW QUESTION: 74

A developer needs to use the CONTIF function to process data entered by the user in an OmniScript. The output of the function needs to be displayed to the user immediately in the current step.

Based on best practice, what element should the developer use this function in?

- A. A Calculation Action element
- B. A SetValues element
- C. A formula element
- D. A Range element

**Answer: C** ([LEAVE A REPLY](#))

Explanation

A formula element allows the developer to define formulas using functions and operators to manipulate data in an OmniScript. The output of the formula element can be displayed to the user

immediately in the current step using a display element. The CONTIF function counts how many times a value appears in a list1. A Calculation Action element executes a calculation procedure and returns the output as a JSON object. A Set Values element assigns values to variables or fields in an OmniScript. A Range element defines a range of values for a variable or field in an OmniScript1. Based on best practice, a formula element is the most suitable element to use the CONTIF function in this scenario.

#### NEW QUESTION: 75

A developer is creating a FlexCard for a new Community page. The FlexCard will display case information along with actions to close the case and update the case, and it will be styled using the Community's theme.

What must the developer do to configure the FlexCard for deployment in a community?

- A. Set the Deployment property in Card Configuration to "Community"
- B. Add the FlexCard's API name to the FlexCard Player component
- C. Set the Target property in Publish Options to "CommunityPage"
- D. Configure the Component Visibility in the Custom Component

**Answer: B** ([LEAVE A REPLY](#))

Explanation

The FlexCard Player component is used to display FlexCards in a community page. The developer needs to add the FlexCard's API name to the FlexCard Player component to configure the FlexCard for deployment in a community.

#### NEW QUESTION: 76

In a calculation procedure, what is required for the output of a calculation step to be used in an aggregation step?

- A. It must be a calculation step.
- B. It must be included in the calculation output.
- C. It must be a matrix lookup step.
- D. It must be included in constants.

**Answer: B** ([LEAVE A REPLY](#))

**Valid OmniStudio-Developer Dumps** shared by TrainingDump.com for Helping Passing OmniStudio-Developer Exam! TrainingDump.com now offer the **newest OmniStudio-Developer exam dumps**, the TrainingDump.com OmniStudio-Developer exam **questions have been updated** and **answers have been corrected** get the **newest** TrainingDump.com OmniStudio-Developer dumps with Test Engine here:

<https://www.trainingdump.com/Salesforce/OmniStudio-Developer-practice-exam-dumps.html>

(107 Q&As Dumps, **40%OFF** Special Discount: **Exam-Tests**)

### NEW QUESTION: 77

A developer needs to configure a calculation procedure to calculate the sum of the entire base price.

What is the most efficient way for the developer to meet this requirement?

- A. Create a Postprocessor apex class to calculate the sum.
- B. Add an Aggregation Step as SUM (BasePrice)
- C. Add A Calculation Step as SUM (BasePrice).
- D. Create a Preprocessor class to calculate the sum

**Answer: B** ([LEAVE A REPLY](#))

Explanation

The Aggregation Step in a calculation procedure allows the developer to perform aggregate functions such as SUM, COUNT, MIN, MAX, and AVG on the output of a previous step. The developer can use this step to calculate the sum of the entire base price by specifying the field name and the aggregation function

### NEW QUESTION: 78

A developer is configuring an integration Procedure Action in an OmniScript. The Omniscript needs a JSON response from the Integration Procedure but does not need to wait for the response for the user to proceed.

Which feature should the developer enable?

- A. Toast Completion
- B. Use Future
- C. Invoke Mode Fire and Forget
- D. Invoke Mode Non-Blocking

**Answer: C** ([LEAVE A REPLY](#))

Explanation

The Invoke Mode Fire and Forget feature enables the OmniScript to invoke the Integration Procedure without waiting for a response. This is useful when the response is not needed for the user to proceed

### NEW QUESTION: 79

In an Integration Procedure, a developer needs to perform a multi-step calculation on every element of an array.

Based on best practices, what two methods are recommended?

Choose 2 answers

- A. Use a Set Values Element inside a Loop Block.
- B. Use a Decision Matrix Action to call a Decision Matrix.
- C. Use a List Action to merge the array elements together.
- D. Use an Expression Set Action to call an Expression Set.

**Answer: A,D** ([LEAVE A REPLY](#))

Explanation

A Set Values Element inside a Loop Block can be used to perform a calculation on each element of an array and store the result in a variable. An Expression Set Action can be used to call an Expression Set that contains one or more expressions to perform calculations on array elements. These two methods are recommended based on best practices for performing multi-step calculations on array elements.

**NEW QUESTION: 80**

Which statement about a FlexCard is true?

- A. A FlexCard can have multiple states.
- B. A FlexCard requires its own data source.
- C. A FlexCard must have test data source settings.
- D. A FlexCard requires a template to be assigned to it

**Answer: D** ([LEAVE A REPLY](#))

**NEW QUESTION: 81**

A customer sets up to LWC Omniscripts, one embedded into another. Account is set in a Set Values element in the parent Omniscript.

The AccountId set in the parent Omniscript is used to another Set Values element ContextAccountId in the embedded OmniScript. The embedded Omniscript is activated.

While previewing the OmniScript flow from the parent, it is found that Account is set correctly in the parent OmniScript. However, ContextAccountId in the embedded OmniScript is not set with the AccountId from parent Omniscript. On previewing the embedded OmniScript individually, it is found that ContextAccountId is set correctly.

What is the reason for this? Refer to the exhibit below.

- A. Both parent and embedded OmniScripts have the same element name for the Set values element.
- B. A developer failed to include a Navigation Element to pass data from the parent OmniScript.
- C. The LWC PubSub Message flag in the Set Values action of the parent has not been set.
- D. The flag passDataJSON in the parent OmniScript is not configured correctly.

**Answer: (**[SHOW ANSWER](#)**)**

Explanation

The LWC PubSub Message flag in the Set Values action of the parent OmniScript enables the parent OmniScript to send data to the embedded OmniScript using a custom event. If this flag is not set, the data will not be passed to the embedded OmniScript.

**NEW QUESTION: 82**

Refer to the exhibit below. In this Integration Procedure structure, what Send JSON Path would you use to send the output of the ActionZ element to a Response Action?

- A. BlockX.BlockYActionZ
- B. ActionZ:BlockY:BlockX
- C. ActionZ:BlockY:BlockX

D. BlockX:BlockY:ActionAZ

**Answer: A ([LEAVE A REPLY](#))**

Explanation

The Send JSON Path syntax for accessing an element from an Integration Procedure structure is BlockName.ElementName. In this case, the BlockName is BlockX and the ElementName is ActionZ. The colon (:) is used to separate the input and output parameters, not the block and element names. The order of the block and element names should follow the hierarchy of the structure, from top to bottom.

### NEW QUESTION: 83

Refer to the exhibit below.

In this Integration Procedure structure, which Send JSON Path should be used to send the output of the Action1 element to a Remote Action?

A. BlockA.BlockB.Action1

B. BlockA:BlockB:Action1

C. Action1:BlockB:BlockA

D. Action1.BlockB.BlockA

**Answer: A ([LEAVE A REPLY](#))**

In OmniStudio Integration Procedures, when you want to reference the output of an element in a nested block (e.g., for use in a Remote Action or another step), you must use dot notation that mirrors the block structure hierarchy.

In the exhibit:

\* Action1 is nested inside:

\* BlockB, which is nested inside:

\* BlockA

Therefore, the correct Send JSON Path to access the result of Action1 is:

CopyEdit

BlockA.BlockB.Action1

This format complies with the standard output reference syntax in Integration Procedures, which follows the pattern:

php-template

CopyEdit

<ParentBlock>.<ChildBlock>.<ActionElement>

Incorrect Options:

\* B. BlockA:BlockB:Action1 - Uses colons instead of dots. This is invalid syntax in JSON path resolution within Integration Procedures.

\* C. Action1:BlockB:BlockA - Incorrect order and invalid separators.

\* D. Action1.BlockB.BlockA - Incorrect order (reversed path).

Reference:

Salesforce OmniStudio Developer Guide # Integration Procedure Element JSON Pathing Best Practices for Send JSON Path # Nested Blocks and Element Referencing

**NEW QUESTION: 84**

Which Calculation Matrix Version in the list would execute on 2/15/2020 at 12:00 PM?

- A. Version Number 3
- B. Version Number 4
- C. Version Number 2
- D. Version Number 1

**Answer: B** ([LEAVE A REPLY](#))

**NEW QUESTION: 85**

Refer to the exhibit.

The card layout uses an integration Procedure as a data source. The cards use the layout data source.

Which JSON data structure supports this card layout and follows best practices?

- A)
- B)
- C)

- A. Option A
- B. Option B
- C. Option C

**Answer: (**[SHOW ANSWER](#)**)**

**NEW QUESTION: 86**

Refer to the exhibit.

What JSON from the DRGetAccountDetails action would display all six values correctly in the OmniScript structure shown? BlkContacts is a Repeat Block.

- A.
- B.
- C.
- D.

**Answer: (**[SHOW ANSWER](#)**)**

According to the OmniScript Data JSON page, the OmniScript structure JSON defines the data elements and their properties that are used in an OmniScript. The exhibit shows an OmniScript structure JSON with six elements: AccountName, AccountNumber, AccountType, AccountOwner, ContactName, and ContactPhone.

The DRGetAccountDetails action is a DataRaptor Extract action that retrieves data from the Account and Contact objects in Salesforce. The BlkContacts element is a Repeat Block that displays a list of contacts related to the account. Therefore, the JSON from the DRGetAccountDetails action that would display all six values correctly in the OmniScript structure shown is option C, which has the following structure:

{The other options have different structures that do not match the OmniScript structure shown. Therefore, the correct answer is C.

#### NEW QUESTION: 87

Refer to the exhibit.

All inputs to the Calculation Matrix are set correctly.

The Calculation Matrix has the following input:

What is the output?

- A. 13.99
- B. 12.99
- C. Null
- D. 12.99,13.99

Answer: B ([LEAVE A REPLY](#))

#### NEW QUESTION: 88

In an Integration Procedure, a developer needs to perform a multi-step calculation on every element of an array.

Based on best practices, what two methods are recommended?

Choose 2 answers

- A. Use a ListAction to merge the array elements together.
- B. Use a Calculation Action to call a Calculation Procedure.
- C. Use a Set Values Element inside a Loop Block.
- D. Use a Matrix Action to call a Calculation Matrix.

Answer: ([SHOW ANSWER](#))

Explanation

According to the Integration Procedure Actions page, a Calculation Action can be used to "call a Calculation Procedure that performs calculations on input data" and a Matrix Action can be used to "call a Calculation Matrix that performs calculations on input data".

#### NEW QUESTION: 89

An OmniScript displays data from an API using Integration Procedure, but some of the data is missing.

Which two configuration errors could cause this? Choose 2 answers

- A. The element name for the missing data does not match the JSON node key in the Integration Procedure Response.
- B. The Integration Procedure Preview Input Parameters do not match the JSON sent from the OmniScript.
- C. The JSON sent from the Integration Procedure Action does not match any of the Original Input for the Integration Procedure
- D. The missing data is trimmed in the Integration Procedure Action Response JSON Path.

Answer: A,C ([LEAVE A REPLY](#))



### Explanation

The element name for the missing data must match the JSON node key in the Integration Procedure Response, otherwise the data will not be mapped correctly. The JSON sent from the Integration Procedure Action must match one of the Original Input for the Integration Procedure, otherwise the Integration Procedure will not execute properly. The Integration Procedure Preview Input Parameters and the Response JSON Path have no effect on displaying data in OmniScript.

### NEW QUESTION: 90

A developer is building an OmniScript and needs to retrieve data from Salesforce and from an on-premises billing database.

Which two OmniScript elements could retrieve this data?

Choose 2 answers

- A. Navigate Action
- B. DataRaptor Extract Action
- C. HTTP Action
- D. Response Action

**Answer: B,C** ([LEAVE A REPLY](#))

### Explanation

According to the OmniScript Action Elements page, a DataRaptor Extract Action can be used to "get data from one or more Salesforce records" and an HTTP Action can be used to "get, save, or delete data through a web application programming interface (API)".

### NEW QUESTION: 91

An integration procedure contains a Remote Action element that calls a method of an APEX class. The method requires two fields as input: AccountId and ProductId. The integration Procedure data JSON contains the following nodes:

How should the Remote Action element be configured to pass the data correctly to the method?

- A. Check the DataRaptor Transform checkbox, and add the following Key/Value pairs to Output JSON Path:
- B. Check the Send Only Additional Input checkbox, and the following/ value pairs to Additional input:
- C. Set Return Only Additional Output to true, and add the following Key/Value pairs to additional input.
- D. Add the following to Send JSON Path: accountId: %AccountId% ProductId% Details Products%

**Answer: C** ([LEAVE A REPLY](#))

**Valid OmniStudio-Developer Dumps** shared by TrainingDump.com for Helping Passing OmniStudio-Developer Exam! TrainingDump.com now offer the **newest OmniStudio-Developer exam dumps**, the TrainingDump.com OmniStudio-Developer exam **questions**

**have been updated and answers have been corrected** get the **newest** TrainingDump.com OmniStudio-Developer dumps with Test Engine here:  
<https://www.trainingdump.com/Salesforce/OmniStudio-Developer-practice-exam-dumps.html>  
(107 Q&As Dumps, **40%OFF** Special Discount: **Exam-Tests**)

#### NEW QUESTION: 92

A developer examines data received from an external data source. The data is nested two levels down in the JSON structure.

Which OmniStudio tool could the developer use to simplify this data?

- A. A guided workflow
- B. A DataRaptor Transform
- C. An HTTP Action Element
- D. An integration Procedure

**Answer: B** ([LEAVE A REPLY](#))

A DataRaptor Transform can simplify nested data by transforming it into a flat structure. The developer can use JSON paths to map the input data to the output data and define the output structure.

#### NEW QUESTION: 93

An integration procedure contains a Remote Action element that calls a method of an APEXclass. The method requires two fields are input: AccountId and ProductId. The integration Procedure data JSON contains the following nodes:

How should the Remote Action element be configured to pass the data correctly to the method?

- A. Check the Send OnlyAdditional Input checkbox, and the following/ value pairs to Additional input:
- B. Set Return Only Additional Output to true, and add the following Key/Value pairs to additional input.
- C. Check the DataRaptor Transform checkbox, and add the following Key/Value pairs to Output JSON Path:
- D. Add the following to Send JSON Path: accountId: %AccountId% ProductId% Details Products%

**Answer: A** ([LEAVE A REPLY](#))

Explanation

Checking the Send Only Additional Input checkbox allows the Remote Action element to send only the key/value pairs specified in Additional input to the Apex method. The Additional input should have the same keys as the method parameters, and the values should be set to {{InputData.node}} for each node. For example, AccountId: {{InputData.AccountId}} and ProductId: {{InputData.Details.Products}}.

#### NEW QUESTION: 94

A developer is creating a FlexCard and needs to display additional information using a Flyout. Which two types of components can the developer embed in the flyout?

Choose 2 answer

- A. An OmniScript
- B. An Integration Procedure
- C. A DataRaptor
- D. A Child FlexCard

**Answer: A,D ([LEAVE A REPLY](#))**

An OmniScript and a Child FlexCard are both valid components that can be embedded in a flyout. An Integration Procedure and a DataRaptor are not components, but actions that can be performed within an OmniScript or a FlexCard.

#### NEW QUESTION: 95

A developer is creating an OmniScript that provisions trail orgs to their customers. The following text block in the Omniscript uses a merge code to display the ID for the new trail org:

- A. To %sDetails: Customer|0: ID\$
- B. To %Details: Customer|1: ID%
- C. To %%%sDetails: Customer|0: ID%%%
- D. To %Details: Customer|n: ID%

**Answer: ([SHOW ANSWER](#))**

The correct syntax for merge codes in OmniScript is %%%sNodeName%%, where NodeName is the name of the JSON node in the data source. The other options are either missing the s or using incorrect symbols.

#### NEW QUESTION: 96

You are importing a list of new products into Salesforce and need to map the new product to the appropriate PriceBook Entries.

What type of DataRaptor mapping keeps track of the new product Records as they are created to use in the Price entries you need to create?

- A. Lookup Mapping
- B. Relationship Query
- C. Lookup Key
- D. Linked Mapping

**Answer: ([SHOW ANSWER](#))**

#### NEW QUESTION: 97

Refer to the exhibit below. What is the merge code needed for this Integration Procedure structure to pass a CaseData node from the HTTP Action's output to the DataRaptor Transform Action?

- A. {{ HTTPGetCaseDetails:CaseData }}
- B. %HTTPGetDetails:CaseData%
- C. %DRXformCaseData: CaseData%
- D. {{CaseData}}

**Answer: C** ([LEAVE A REPLY](#))

#### NEW QUESTION: 98

Refer to the exhibit.

A developer has configured an integration Procedure element with SEND/RESPONSE TRANSFORMATIONS as shown.

Alternatively, how could the developer configure Additional input to send exactly the same data? Assume that the developer checked Send Only Additional input.

A.

B.

C.

**Answer: (**[SHOW ANSWER](#)**)**

Explanation

Option C is the correct way to configure Additional input to send exactly the same data as Input Data. The Additional input should have a key/value pair for each field in Input Data, and the value should be set to

{{InputData.field}} for each field. This will pass the value of Input Data for each field to Additional input.

#### NEW QUESTION: 99

What are two items you can include on a flyout action? Choose 2 answers

A. Another flyout

B. A link to an Integration Procedure

C. A link to a DataRaptor Load

D. An OS Action

**Answer: B,D** ([LEAVE A REPLY](#))

#### NEW QUESTION: 100

A developer is creating an OmniScript that provisions trail orgs to their customers. The following text block in the Omniscript uses a merge code to display the ID for the new trail org:

A. To %sDetails: Customer|0: ID\$

B. To %Details: Customer|1: ID%

C. To %sDetails: Customer|0: ID%%

D. To %Details: Customer|n: ID%

**Answer: B** ([LEAVE A REPLY](#))

The correct syntax for merge codes in OmniScript is %sNodeName%, where NodeName is the name of the JSON node in the data source. The other options are either missing the s or using incorrect symbols.

#### NEW QUESTION: 101

A developer builds a new OmniScript. It contains a Set Values element with a ContextId key/value pair that was used during testing.

What should the developer do before moving the OmniScript to a production org?

- A. Update the ContextId value to specify an id from the Production org.
- B. Add a Show/Hide condition on the Set Values element.
- C. Delete or Deactivate the Set Values element.
- D. Deactivate the contextId key/value pair

**Answer: C** ([LEAVE A REPLY](#))

Explanation

The Set Values element with a ContextId key/value pair was used for testing purposes and is not needed for production. The developer should delete or deactivate the Set Values element before moving the OmniScript to a production org.

### NEW QUESTION: 102

In an Expression Set, what is required for the output of a Calculation Step to be used in an Aggregation Step?

- A. It must be included in constants.
- B. It must be included in the output.
- C. It must be a calculation step.

**Answer: B** ([LEAVE A REPLY](#))

In Expression Sets, for any intermediate step (like Calculation) to be referenced in subsequent steps, such as Aggregation, the value must be made available via Output.

\* B. It must be included in the output - Correct. Each step has an "Include in Output" checkbox. If not checked, its result is not accessible to following steps like Aggregation or Sub Expression.

Incorrect Options:

- \* A. Constants are global but do not affect step dependency.
- \* C. It does not have to be a Calculation Step; any previous step's output can be used if exposed.

:

Salesforce OmniStudio # Expression Sets - Step Configuration

### NEW QUESTION: 103

Refer to the following row-versioned calculation matrix.

The developer needs to delete the row that contains the Code CA-SF.

If the developer deletes that row in Version 3, what is the result?

- A. The row is deleted only in Version 3.
- B. The row is deleted In Versions 2 and 3 but will remain in Version 1.
- C. The row is deleted in Version 3 and Version 1.
- D. The row is deleted in all versions

**Answer: A** ([LEAVE A REPLY](#))

Deleting a row in Version 3 will only affect that version, not any previous or future versions. The row that contains the Code CA-SF will remain in Versions 1 and 2, as well as any versions

created after Version 3. The other options are incorrect because they imply that deleting a row in one version will affect other versions as well.

#### NEW QUESTION: 104

A developer creates a FlexCard that displays a contact's mailing address and passes the contact's postal code to a child FlexCard.

When configuration text elements in the child FlexCard, what syntax should a developer use to refer to the contact's postal code?

- A. {Postalcode}
- B. {Parent.postalcode}
- C. {Records.postalcode}
- D. {Params.postalcode}

**Answer: D** ([LEAVE A REPLY](#))

The Params node contains the data that is passed from the parent FlexCard to the child FlexCard. The developer should use {Params.postalcode} to refer to the contact's postal code in the child FlexCard.

#### NEW QUESTION: 105

Refer to the exhibit below. What is the merge code needed for this Integration Procedure structure to pass a CaseData node from the HTTP Action's output to the DataRaptor Transform Action?

- A. %HTTPGetDetails:CaseData%
- B. %DRXformCaseData: CaseData%
- C. {{ HTTPGetCaseDetails:CaseData }}
- D. {{CaseData}}

**Answer: C** ([LEAVE A REPLY](#))

Explanation

The merge code syntax for accessing a node from an Integration Procedure output is {{ProcedureName:NodeName}}. In this case, the ProcedureName is HTTPGetCaseDetails and the NodeName is CaseData. The % sign is used for single-value merge codes, not node merge codes. The \$ sign is used for variables, not merge codes.

#### NEW QUESTION: 106

A developer creates a DataRaptor Extract to retrieve data to pass to an external service. The external service expects the field value to be an integer. However, the DataRaptor is sending it as a string.

Which action can the developer take to fix this?

- A. In the DataRaptor Output tab, select the Output Data Type of that field to Integer.
- B. In the DataRaptor Output tab, enter the default value as 0 on the field.
- C. In the DataRaptor Extract tab, set the Input Data Type field to Integer.

**D.** In the DataRaptor Formula tab, define a formula using the function TOINTEGER and use the formula as output.

**Answer:** ([SHOW ANSWER](#))

The DataRaptor Formula tab allows the developer to define formulas using functions and operators to manipulate data. The TOINTEGER function converts a string value to an integer value. The developer can use this function to output the field value as an integer and use the formula as output.

**Valid OmniStudio-Developer Dumps** shared by TrainingDump.com for Helping Passing OmniStudio-Developer Exam! TrainingDump.com now offer the **newest OmniStudio-Developer exam dumps**, the TrainingDump.com OmniStudio-Developer exam **questions have been updated** and **answers have been corrected** get the **newest** TrainingDump.com OmniStudio-Developer dumps with Test Engine here:

<https://www.trainingdump.com/Salesforce/OmniStudio-Developer-practice-exam-dumps.html>

(107 Q&As Dumps, **40%OFF** Special Discount: **Exam-Tests**)

#### **NEW QUESTION: 107**

A developer creates a new FlexCard to display customer data and actions, such as updating billing information and changing the contact for the customer account. The FlexCard contains 10 fields and 5 actions.

During testing, several fields display with the correct data, but one of the fields shows only the label.

What could cause this?

- A.** The field is null in the Salesforce record.
- B.** The fields have exceeded the maximum number allowed on the card.
- C.** There are no test parameters configured.
- D.** {recordId} is misspelled in the Data Source Input Map.

**Answer:** B ([LEAVE A REPLY](#))

#### **NEW QUESTION: 108**

A developer needs to transform contact data into a JSON array.

Given the input JSON shown above, what are two ways a developer could configure a DataRaptor transform to achieve the expected Output JSON? Choose 2 answers

- A.** Use a formula LIST(Contact), and add the output of the formula as the input in the Transform tab.
- B.** Set the input JSON Path as Contact and the Output JSON Path as List (Contact)
- C.** Set the Input JSON path as List(Contact) and the Output JSON Path as Contact.
- D.** Set the Input JSON Path as Contact the output JSON Path as contact and output Data type as List.

**Answer: C,D ([LEAVE A REPLY](#))**

#### **NEW QUESTION: 109**

A developer needs to create a list of cases for an account in a single Datable in a FlexCard. Like the one shown below.

How can the developer configure the FlexCard to display the case records in this way?

- A.** Enable the record Looping feature on the data table elements
- B.** Select the Repeatable Mode property on the data table elements
- C.** Enable the Repeat Records feature on the FlexCard Setup tab
- D.** Disable the Repeat Record feature on the FlexCard setup tab

**Answer: B ([LEAVE A REPLY](#))**

The Repeatable Mode property on the data table elements allows the developer to display multiple records in a single data table. The Repeat Records feature on the FlexCard Setup tab is used to display multiple FlexCards for each record in a data source. The Record Looping feature on the data table elements is used to iterate over a list of records and perform actions on each record. The Overwrite Target for all Null input checkbox on the Account id field is used to overwrite the existing value in the target object with null if the input value is null.

#### **NEW QUESTION: 110**

A developer is configuring a DataRaptor Load to Save contract data. The developer needs to set the record type of the contact using DeveloperName.

Which two configuration actions should the developer take to set this up in the DataRaptor Load?

- A.** Select RecordType in the Lookup object list. Development in the lookup Field list, and ID in the Lookup Requested Field list.
- B.** Add Link to RecordType object in the Contact Object with the id field of RecordType object.
- C.** Check is Lookup property when mapping the fields.
- D.** Select RecordType in the Lookup Object list. ID in the Lookup Field list, and Development in the Lookup requestedField list.

**Answer: ([SHOW ANSWER](#))**

#### **NEW QUESTION: 111**

A)

B)

**A.** Option A

**B.** Option B

**Answer: A ([LEAVE A REPLY](#))**

#### **NEW QUESTION: 112**

An integration procedure contains a Remote Action element that calls a method of an APEX class. The method requires two fields are input: Accountid and ProductId. The integration Procedure data JSON contains the following nodes:



How should the Remote Action element be configured to pass the data correctly to the method?

- A. Check the Send Only Additional Input checkbox, and the following/ value pairs to Additionalinput:
- B. Add the following to Send JSON Path: accountId: %Accountd% ProductId% Details Products%
- C. Set Return Only Additional Output to true, and add the following Key/Value pairs to additional input.
- D. Check the DataRaptor Transform checkbox, and add the following Key/Value pairs to Output JSON Path:

**Answer:** ([SHOW ANSWER](#))

### NEW QUESTION: 113

Refer to the exhibit.

The card layout uses an integration Procedure as a data source. The cards use the layout data source.

Which JSON data structure supports this card layout and follows best practices?

- A)
- B)
- C)
- A. Option A
- B. Option C
- C. Option B

**Answer:** ([SHOW ANSWER](#))

**Valid OmniStudio-Developer Dumps** shared by TrainingDump.com for Helping Passing OmniStudio-Developer Exam! TrainingDump.com now offer the **newest OmniStudio-Developer exam dumps**, the TrainingDump.com OmniStudio-Developer exam **questions have been updated** and **answers have been corrected** get the **newest** TrainingDump.com OmniStudio-Developer dumps with Test Engine here:

<https://www.trainingdump.com/Salesforce/OmniStudio-Developer-practice-exam-dumps.html>

(107 Q&As Dumps, **40%OFF** Special Discount: **Exam-Tests**)